





# Kugelhahnen 3/2 und 3/3-Wege




## Kugelhahn 3/3 Wege vertikal mit L-Bohrung

3 Gewinde, 3 Positionen für maximale Flexibilität.

Messing verchromt, Griff Kunststoff schwarz, Kontermutter. Temperatur -20/+80° C, Druck -0.95/+13 bar.




Artikel	G1	D1 (DN)	A1	A2	A3	A4	SW1	SW2	VP1	VE	VP2
15.130	G 1/8	5 mm	35 mm	19 mm	33.5 mm	15.5 mm	SW17	SW17	16.90	25	15.30
15.131	G 1/4	5 mm	37 mm	19 mm	33.5 mm	17.5 mm	SW17	SW17	17.90	25	16.20
15.134	G 3/8	7 mm	42 mm	19 mm	35 mm	19.5 mm	SW17	SW21	19.80	10	17.90




## Kugelhahn 3/3 Wege vertikal mit T-Bohrung

3 Gewinde, 3 Positionen für maximale Flexibilität.

Messing verchromt, Griff Kunststoff schwarz, Kontermutter. Temperatur -20/+80° C, Druck -0.95/+13 bar.




Artikel	G1	D1 (DN)	A1	A2	A3	A4	SW1	SW2	VP1	VE	VP2
15.132	G 1/8	5 mm	35 mm	19 mm	33.5 mm	15.5 mm	SW17	SW17	16.90	25	15.30
15.133	G 1/4	5 mm	37 mm	19 mm	33.5 mm	17.5 mm	SW17	SW17	17.20	25	16.20
15.135	G 3/8	7 mm	42 mm	19 mm	35 mm	19.5 mm	SW17	SW21	19.00	10	17.90



## Kugelhahn 3/2 Wege horizontal mit L-Bohrung

3 Gewinde, 2 Positionen Messing vernickelt.

Temperatur -20/+80° C, Druck -0.99/+16 bar.



Artikel	G1	D1 (DN)	A1	A2	A3	A4	D2	VP1
40.292	G 1/2	15 mm	77 mm	19 mm	125 mm	85 mm	39 mm	58.30
40.293	G 3/4	20 mm	92 mm	23 mm	145 mm	107 mm	47 mm	96.80
40.294	G 1	25 mm	104 mm	25 mm	170 mm	124 mm	55 mm	145.20