



### T - Verschraubung mit zylindrischem Innengewinde

Betriebsdruck -0.99 bis >70 bar,  
für Druckluft, Wasser, Schmierung.

Geeignet für Rohre aus Kupfer, Stahl, Alu - bei Kunststoff-  
rohr Stützhülse verwenden.

Artikel	D1	G1	A2	A3	SW1	VP1	VE	VP2
24.804/041	4 mm	G 1/8	45 mm	18 mm	SW8	2.50	50	2.21
24.804/061	6 mm	G 1/8	47.5 mm	19.5 mm	SW9	2.70	50	2.39
24.804/062	6 mm	G 1/4	56 mm	24.5 mm	SW13	3.55	50	3.13
24.804/081	8 mm	G 1/8	57 mm	19.5 mm	SW12	3.15	50	2.76
24.804/082	8 mm	G 1/4	59 mm	24.5 mm	SW13	3.65	50	3.22
24.804/102	10 mm	G 1/4	64 mm	24.5 mm	SW13	4.30	25	3.77
24.804/103	10 mm	G 3/8	58 mm	26 mm	SW14	4.80	25	4.23
24.804/104	10 mm	G 1/2	69 mm	26 mm	SW15	5.65	25	4.97
24.804/122	12 mm	G 1/4	69 mm	25.5 mm	SW14	5.65	25	4.97
24.804/123	12 mm	G 3/8	69 mm	26 mm	SW14	5.65	25	4.97
24.804/124	12 mm	G 1/2	70 mm	26 mm	SW15	6.35	25	5.61
24.804/144	14 mm	G 1/2	77 mm	30 mm	SW18	7.50	25	6.62
24.804/154	15 mm	G 1/2	78 mm	30 mm	SW18	7.50	25	6.62
24.804/164	16 mm	G 1/2	77.5 mm	28.5 mm	SW17	8.95	10	7.91
24.804/184	18 mm	G 1/2	83 mm	28 mm	SW20	10.75	10	9.48
24.804/185	18 mm	G 3/4	83 mm	34 mm	SW20	11.65	10	10.30