




Schlauchanschlüsse Stahl verzinkt




Schlauchanschluss Stahl verzinkt mit Innengewinde, einteilig

Druck für Flüssigkeiten bis 20 bar, für Druckluft bis 15 bar.

-20 / +140° C.

Artikel	G1	Für Schlauch	A1	D1	SW1	VP1	VE	VP2
37.945	G 1/8	LW 6 mm	45.5 mm	7 mm	SW14	3.45	10	2.66
37.946	G 1/8	LW 8 mm	45.5 mm	9 mm	SW14	3.45	10	2.66
37.947	G 1/8	LW 10 mm	45.5 mm	11 mm	SW14	3.45	10	2.66
37.948	G 1/4	LW 6 mm	41.5 mm	7 mm	SW16	3.45	10	2.66
37.949	G 1/4	LW 8 mm	41.5 mm	9 mm	SW16	3.45	10	2.66
37.950	G 1/4	LW 10 mm	41.5 mm	11 mm	SW16	3.45	10	2.66
37.951	G 1/4	LW 13 mm	45.5 mm	13.5 mm	SW16	3.45	10	2.66
37.952	G 3/8	LW 8 mm	45.5 mm	9 mm	SW19	5.00	10	3.83
37.953	G 3/8	LW 10 mm	45.5 mm	11 mm	SW19	5.00	10	3.83
37.954	G 3/8	LW 13 mm	45.5 mm	13.5 mm	SW19	5.00	10	3.83



Schlauchverbinder Stahl verzinkt

Druck für Flüssigkeiten bis 20 bar, für Druckluft bis 15 bar.

-20 / +140° C.

Artikel	Für Schlauch	A1	A2	D1	D2	VP1	VE	VP2
40.540	LW 6 mm	52 mm	5 mm	7 mm	9 mm	3.65	10	2.83
40.541	LW 8 mm	52 mm	5 mm	9 mm	11 mm	3.65	10	2.83
40.542	LW 10 mm	52 mm	5 mm	11 mm	13 mm	3.65	10	2.83
40.543	LW 13 mm	52 mm	5 mm	13 mm	15 mm	6.05	10	4.66
40.544	LW 16 mm	52 mm	5 mm	16.5 mm	17 mm	7.60	10	5.49