




Raccords pour tuyaux acier galvanisé



Raccord pour tuyaux, filetage mâle cylindrique

Pression pour liquides jusqu'à 20 bar, pour air comprimé 15 bar.

-20 / +140° C.

Article	G1	Pour tuyau int.	A1	A2	D1	D2	SW1	VP1
40.590	G 1/8	LW 4	38.5 mm	27.5 mm	5 mm	2 mm	SW12	3.75
40.620	G 1/8	LW 6	34.5 mm	23.5 mm	7 mm	3 mm	SW12	2.30
40.621	G 1/8	LW 8	38.5 mm	27.5 mm	9 mm	5 mm	SW12	2.50
40.622	G 1/8	LW 10	42.5 mm	27.5 mm	11 mm	5 mm	SW16	2.30
40.591	G 1/4	LW 4	38.5 mm	23.5 mm	5 mm	2 mm	SW16	2.85
40.625	G 1/4	LW 6	38.5 mm	23.5 mm	7 mm	3 mm	SW16	2.20
40.626	G 1/4	LW 8	38.5 mm	23.5 mm	9 mm	5 mm	SW16	2.20
40.627	G 1/4	LW 10	38.5 mm	23.5 mm	11 mm	7 mm	SW16	2.20
40.628	G 1/4	LW 13	42.5 mm	27.5 mm	13 mm	8 mm	SW16	2.40
40.630	G 3/8	LW 8	41 mm	23.5 mm	9 mm	5 mm	SW22	3.65
40.631	G 3/8	LW 10	41 mm	23.5 mm	11 mm	7 mm	SW22	3.65
40.632	G 3/8	LW 13	45 mm	27.5 mm	13 mm	8 mm	SW22	3.95
40.633	G 3/8	LW 16	58 mm	40 mm	16.5 mm	10 mm	SW22	4.20
40.635	G 1/2	LW 16	59 mm	40 mm	16.5 mm	10 mm	SW25	6.55
40.636	G 1/2	LW 19	59 mm	40 mm	20 mm	13 mm	SW25	6.70
40.637	G 3/4	LW 19	59 mm	40 mm	20 mm	13 mm	SW30	7.10