





Armatures en laiton nickelé



Tubulures doubles en laiton nickelé avec filetages coniques

Article	G1	G2	A1	A2	A4	SW1	VP1	VE	VP2
38.674/VK	M5	M5	4 mm	4 mm	11.5 mm	SW8	0.75	50	0.64
38.680/VK	G 1/8	G 1/8	7.5 mm	7.5 mm	19.5 mm	SW12	0.95	50	0.83
38.670/VK	G 1/8	G 1/4	7.5 mm	11 mm	23.5 mm	SW14	1.15	50	1.01
38.681/VK	G 1/4	G 1/4	11 mm	11 mm	27 mm	SW14	1.15	50	1.01
38.684/VK	G 1/4	G 3/8	11 mm	11.5 mm	27.5 mm	SW17	1.70	25	1.47
40.890/VK	G 1/4	G 1/2	11 mm	14 mm	30.5 mm	SW22	2.60	25	2.30
38.682/VK	G 3/8	G 3/8	11.5 mm	11.5 mm	28 mm	SW17	1.70	100	1.47
40.891/VK	G 3/8	G 1/2	11.5 mm	14 mm	31 mm	SW22	2.60	25	2.30
38.683/VK	G 1/2	G 1/2	14 mm	14 mm	33.5 mm	SW22	2.60	25	2.30
40.892/VK	G 1/2	G 3/4	15 mm	16.5 mm	37.5 mm	SW27	4.60	25	4.05
40.893/VK	G 3/4	G 3/4	16.5 mm	16.5 mm	40 mm	SW27	4.60	25	4.05
40.886/VK	G 3/4	G 1	16.5 mm	19 mm	43 mm	SW34	9.05	10	8.00
40.887/VK	G 1	G 1	19 mm	19 mm	45.5 mm	SW34	9.05	10	8.00



Bouchon de fermeture avec six pans femelle
Avec filetage cylindrique et O-ring.

Article	G1	A1	D1	SW1	VP1	VE	VP2
43.910/I14	G 1/8	6 mm	14 mm	5 mm	0.95	100	0.70
43.911/I17	G 1/4	8 mm	17 mm	6 mm	1.15	100	0.90
43.912/I20	G 3/8	9 mm	20 mm	8 mm	1.35	100	1.10
43.913/I25	G 1/2	10 mm	25 mm	10 mm	2.30	100	1.90