

## Tuyauterie en ALU pour air comprimé



Manchon mâle en laiton, à serrer

-0.99 à 13 bar.

Article	D1 extérieur	G1	Serrage	VP1
22.542	20 mm	G 1/2	30 Nm	6.60
22.543	25 mm	G 3/4	30 Nm	9.90
22.541	32 mm	G 1	40 Nm	13.20
22.544	40 mm	G 1 1/4	65 Nm	19.80



Manchon mâle en laiton nickelé, modèle „push-in“

-0.99 à 13 bar.

Article	D1 extérieur	G1	VP1
22.442	20 mm	G 1/2	7.90
22.443	25 mm	G 3/4	13.55
22.441	32 mm	G 1	17.30
22.444	40 mm	G 1 1/4	21.50
22.445	50 mm	G 1 1/2	42.10



Manchon femelle en laiton, à serrer

-0.99 à 13 bar.

Article	D1 extérieur	G1	Serrage	VP1
22.552	20 mm	G 1/2	30 Nm	6.90
22.553	25 mm	G 3/4	30 Nm	9.90
22.551	32 mm	G 1	40 Nm	13.75
22.554	40 mm	G 1 1/4	65 Nm	20.60



Manchon femelle en laiton nickelé, modèle „push-in“

-0.99 à 13 bar.

Article	D1 extérieur	G1	VP1
22.452	20 mm	G 1/2	7.60
22.453	25 mm	G 3/4	13.00
22.451	32 mm	G 1	17.30
22.454	40 mm	G 1 1/4	21.50
22.455	50 mm	G 1 1/2	42.10