




# Raccords pour tuyaux en polyamide 66



Raccord pour tuyaux bleu avec filetage mâle conique

Pour une pression de -0.99 à 12.5 bar à 25° C.

Pour air comprimé, vacuum, eau, huiles et émulsions.

| Article | G1    | Pour tuyau int. | A1      | A2    | D1    | SW1  | VP1  | VE  | VP2  |
|---------|-------|-----------------|---------|-------|-------|------|------|-----|------|
| 38.110  | G 1/8 | LW 4            | 30.5 mm | 16 mm | 5 mm  | SW11 | 0.85 | 100 | 0.50 |
| 38.120  | G 1/8 | LW 6            | 37.5 mm | 23 mm | 7 mm  | SW11 | 1.05 | 100 | 0.70 |
| 38.121  | G 1/8 | LW 8            | 39.5 mm | 25 mm | 9 mm  | SW11 | 1.05 | 100 | 0.70 |
| 38.111  | G 1/4 | LW 4            | 33.5 mm | 16 mm | 5 mm  | SW14 | 0.95 | 100 | 0.60 |
| 38.125  | G 1/4 | LW 6            | 40.5 mm | 23 mm | 7 mm  | SW14 | 0.95 | 100 | 0.60 |
| 38.126  | G 1/4 | LW 8            | 42.5 mm | 25 mm | 9 mm  | SW14 | 1.05 | 100 | 0.70 |
| 38.127  | G 1/4 | LW 10           | 44 mm   | 27 mm | 11 mm | SW14 | 1.15 | 100 | 0.80 |
| 38.128  | G 1/4 | LW 13           | 45 mm   | 28 mm | 13 mm | SW14 | 1.25 | 100 | 0.90 |
| 38.129  | G 3/8 | LW 6            | 40.5 mm | 23 mm | 7 mm  | SW17 | 0.95 | 100 | 0.83 |
| 38.130  | G 3/8 | LW 8            | 42.5 mm | 25 mm | 9 mm  | SW17 | 1.05 | 100 | 0.92 |
| 38.131  | G 3/8 | LW 10           | 44 mm   | 27 mm | 11 mm | SW17 | 1.25 | 100 | 1.10 |
| 38.132  | G 3/8 | LW 13           | 45 mm   | 28 mm | 13 mm | SW17 | 1.25 | 100 | 1.10 |
| 38.148  | G 1/2 | LW 8            | 45 mm   | 25 mm | 9 mm  | SW22 | 1.25 | 50  | 1.10 |
| 38.149  | G 1/2 | LW 10           | 46.5 mm | 27 mm | 11 mm | SW22 | 1.50 | 50  | 1.29 |
| 38.134  | G 1/2 | LW 13           | 48.5 mm | 27 mm | 13 mm | SW22 | 1.50 | 50  | 1.29 |
| 38.135  | G 1/2 | LW 16           | 50 mm   | 30 mm | 17 mm | SW22 | 1.50 | 50  | 1.29 |
| 38.136  | G 1/2 | LW 19           | 51 mm   | 31 mm | 20 mm | SW22 | 1.60 | 50  | 1.38 |
| 38.137  | G 3/4 | LW 13           | 48.5 mm | 27 mm | 13 mm | SW27 | 1.50 | 50  | 1.29 |
| 38.138  | G 3/4 | LW 16           | 51 mm   | 30 mm | 17 mm | SW27 | 1.70 | 50  | 1.47 |
| 38.139  | G 3/4 | LW 19           | 52 mm   | 31 mm | 20 mm | SW27 | 1.90 | 50  | 1.66 |