




Schlauchanschlüsse aus Polyamid 66



Schlauchanschluss blau mit konischem Aussengewinde

Für Druck -0.99 bis 12.5 bar bei 25° C.

Für Druckluft, Vakuum, Wasser, Öl und Emulsionen.

Artikel	G1	Für Schlauch	A1	A2	D1	SW1	VP1	VE	VP2
38.110	G 1/8	LW 4 mm	30.5 mm	16 mm	5 mm	SW11	0.85	100	0.50
38.120	G 1/8	LW 6 mm	37.5 mm	23 mm	7 mm	SW11	1.05	100	0.70
38.121	G 1/8	LW 8 mm	39.5 mm	25 mm	9 mm	SW11	1.05	100	0.70
38.111	G 1/4	LW 4 mm	33.5 mm	16 mm	5 mm	SW14	0.95	100	0.60
38.125	G 1/4	LW 6 mm	40.5 mm	23 mm	7 mm	SW14	0.95	100	0.60
38.126	G 1/4	LW 8 mm	42.5 mm	25 mm	9 mm	SW14	1.05	100	0.70
38.127	G 1/4	LW 10 mm	44 mm	27 mm	11 mm	SW14	1.15	100	0.80
38.128	G 1/4	LW 13 mm	45 mm	28 mm	13 mm	SW14	1.25	100	0.90
38.129	G 3/8	LW 6 mm	40.5 mm	23 mm	7 mm	SW17	0.95	100	0.83
38.130	G 3/8	LW 8 mm	42.5 mm	25 mm	9 mm	SW17	1.05	100	0.92
38.131	G 3/8	LW 10 mm	44 mm	27 mm	11 mm	SW17	1.25	100	1.10
38.132	G 3/8	LW 13 mm	45 mm	28 mm	13 mm	SW17	1.25	100	1.10
38.148	G 1/2	LW 8 mm	45 mm	25 mm	9 mm	SW22	1.25	50	1.10
38.149	G 1/2	LW 10 mm	46.5 mm	27 mm	11 mm	SW22	1.50	50	1.29
38.134	G 1/2	LW 13 mm	48.5 mm	27 mm	13 mm	SW22	1.50	50	1.29
38.135	G 1/2	LW 16 mm	50 mm	30 mm	17 mm	SW22	1.50	50	1.29
38.136	G 1/2	LW 19 mm	51 mm	31 mm	20 mm	SW22	1.60	50	1.38
38.137	G 3/4	LW 13 mm	48.5 mm	27 mm	13 mm	SW27	1.50	50	1.29
38.138	G 3/4	LW 16 mm	51 mm	30 mm	17 mm	SW27	1.70	50	1.47
38.139	G 3/4	LW 19 mm	52 mm	31 mm	20 mm	SW27	1.90	50	1.66