





Armatures en laiton nickelé



Tubulures doubles réduites en laiton nickelé avec filetages coniques

Réductions mâles-femelles.

Article	G1	G2	SW1	VP1	VE	VP2
38.622	M5	G 1/8	SW14	1.15	50	1.01
38.625	G 1/8	G 1/4	SW17	1.35	50	1.20
38.626	G 1/4	G 3/8	SW22	2.10	25	1.90
38.627	G 1/4	G 1/2	SW27	3.35	25	3.00
38.615	G 3/8	G 1/2	SW26	3.55	25	3.13
38.616	G 1/2	G 3/4	SW32	7.50	25	6.05



Manchons en laiton nickelé

Réductions femelles-femelles.

Article	G1	G2	SW1	VP1	VE	VP2
38.574	M 5	G 1/8	SW14	1.35	50	1.20
38.575	G 1/8	G 1/8	SW14	1.15	50	1.01
38.635	G 1/8	G 1/4	SW17	1.80	50	1.56
38.636	G 1/8	G 3/8	SW22	2.20	25	1.93
38.576	G 1/4	G 1/4	SW17	1.80	25	1.56
38.637	G 1/4	G 3/8	SW22	2.50	25	2.21
38.577	G 3/8	G 3/8	SW22	2.40	25	2.12
38.638	G 1/4	G 1/2	SW24	2.85	25	2.48
38.639	G 3/8	G 1/2	SW24	3.55	25	3.13
38.578	G 1/2	G 1/2	SW26	3.85	25	3.40
38.629	G 3/4	G 1/2	SW32	6.15	10	5.43